

TECHNICAL INFORMATION FOR

SHIELD

GLASS PROTECTOR



TECHNICAL DATA SHEET

SHIELD PROTECTIVE GLASS FILM

Protective film for glass gives highly effective protection to both internal and external window from plaster and paint splashes etc. during building and decoration works.

Note: Please ensure you have read and fully understood the usage guidelines before installation.



FEATURES



- Protects against dirt, stains, mess & spillages
- Will not move after application
- Waterproof
- Easy to remove
- Reverse wound for easy application
- Full batch traceability
- Date of production printed on inner core

PRODUCT RANGE

Product Code	Thickness (µm)	Width (mm)	Length (m)	Qty	Carton Qty
25WP	50	600	25	1	9
50WP	50	600	50	1	9

APPLICATION

- Ensure all surfaces are free from grease, dust and other contaminants to aid with the adhesion process of application.
- Remove outer packaging from roll.
- Place roll in the direction it is to be applied, and unwind 6 inches (150mm) of material. Ensure that this section has adhered to the glass surface by hand.
- Simply roll along the glass surface using hands, ensuring that it rolls in a straight line.
- Smooth out with hands as it unwinds.

PERFORMANCE DATA

Adhesive	Acrylic
Environmental Condition Temperature	-5°C to 25°C
Relative Humidity	90 ± 10%
Shelf Life	12 months

LIMITATIONS

- Shield Glass Protector is not for use on carpeted or wooden/tiled flooring surfaces.
- For improved adhesion to the glass, the removal of grease, dust and other contaminants is advised.
- Always check that the film has stuck firmly prior to commencing work.
- To check for compatibility, a test area is always recommended prior to full application.
- On some surfaces, Shield Glass Protector may leave a residue, this can be easily removed using Shield Extra Tough Builders Wipes. A test area is always recommended prior to full application.
- In warm, humid environments, remove Shield Glass Protector after 1 week maximum.
- Do not use on surfaces which have a likelihood to bleed oils and plasticizers.
- Remove Shield Glass Protector after a maximum of 30 days, to prevent a sticky residue being left on the glass.
- If in doubt when determining whether Shield Glass Protector is suitable for use, contact TIMco technical support for further advice.

HEALTH & SAFETY

- Consult Safety Data Sheet (SDS03) for full list of hazards.